

Patent

Powerful Light

Professional Lamp

High CRI

Stepless Dimming

Dmx Control

Waterproof

All Weather

Soft Light-Diffusion

Safety



Airpillow Bi24TD - 4X2 Ft

| | |
|-----------------------|---------------------|
| Power | 150W LED |
| TLCI | 98 |
| Balloon Size: cm ft | 125X65X20cm 4X2ft |
| Gross Weight: | 12 kg |
| Package | 60X44X24cm |
| Color: Option | Bicolor |

| No | Color Range | LUX@ 0.5m | LUX@ 1m | LUX@ 2m |
|----|-------------|-----------|---------|---------|
| 1 | 2700K | 7580 | 2910 | 849 |
| 2 | 3200K | 9150 | 3590 | 1028 |
| 3 | 5600K | 10380 | 4320 | 1175 |
| 4 | 6500K | 9700 | 3950 | 1077 |

Airpillow RG24C - 4ft

| | |
|------------------|---------------------|
| Power | 180W LED |
| TLCI | 98 |
| Balloon Size: cm | 125X65X20cm 4X2ft |
| Gross Weight: | 10 kg |
| Package | 52X42X23cm |
| Color: | Bicolor + RGB |

| | | |
|------------------------|--|---|
| Model | Airpillow Bi24TD | AirPillow RG24C |
| Model Image |  |  |
| Lighting | | |
| Lighting Source | BiColor LED | BiColor +RGB LED |
| Joint Standard | LP16-4 | LP16-7 |
| Color Temperature | 2700k-6500K | 2500-20000K |
| Lumen: | | 0.5m:10400L 1m:4420L 2m:1190L |
| Light meter parameters | 0.5m f11 1m f8 2m f5.6 | 0.5m f11 1m f8 2m f5.6 |
| | iso 800 shutter 1/50 | iso 800 shutter 1/50 |
| Power | 150W | 180W |
| Max Power | 300W | |
| CRI/TLCI | 98 | 98 |
| Waterproof | IP 67 | IP 67 |
| Can be Folded | Yes | Yes |

| | | |
|---------------------|------------------------|-----------------------|
| Balloon | | |
| Dimension | 125X65X20cm | 125X65X20cm |
| Weight | 920 g | 1175 g |
| Material | PU Coated | PU Coated |
| Thickness | 0.2mm | 0.2mm |
| Air Valve | 65mm dia 50mm high | 65mm dia 50mm high |
| Side Skirts | Support | Support |
| Grids | Including | Including |
| Airtight | 7 Days | 7 Days |
| Working Temperature | - 10 to 40 degree | - 10 to 40 degree |
| | | |
| Control Unit | | |
| Dimension | 23.5X16X6.5cm | 27X16X6.5cm |
| Material | Aviation aluminum | Aviation aluminum |
| Weight | 1530 g | 1530 g |
| Cable Spec | 3X1.5mm | 3X1.5mm |
| Cable Lenth | 7m | 7m |
| Cable Connection | LP16-4 | LP16-4 |
| Touch Screen | No | No |
| Support | Dmx 512 Wifi Dmx 512 | Dmx 512 Wifi Dmx512 |

| | | |
|-------------------------|--------------|------------------------|
| Control Function | | |
| Dxm Mode | No | Dmx 512 Wifi Dmx 512 |
| Dim Curve | No | Yes |
| Language | English | English Chinese |
| Fan Set | No | Yes |
| | | |
| Lighting Mode | | |
| CCT Mode | No | Yes |
| HSI Mode | No | Yes |
| RGBWY Mode | No | Yes |
| GEL Mode | No | Yes |
| CY Mode | No | Yes |
| FX Mode | No | Yes |
| Stepless Dimming | 0-100% | 0-100% |
| | | |
| Power Supply | | |
| Input Voltage | AC:110-220V/ | AC:110-220V/ |
| Length | 3 m | 3 m |
| V-Battery Connect | DC:16.5V | DC:16.5V |

| | | |
|-----------------------------|------------------|------------------|
| Tripod Stand | | |
| Connection | 1k Pin | 1k Pin |
| | | |
| Safety Case | | |
| Material | Industry Plastic | Industry Plastic |
| Dimension external | 60X44X24cm | 60X44X24cm |
| Dimension Internal | 54X38X21cm | 48X35X20cm |
| Weight | 5 kg | 4.5 kg |
| | | |
| Packing & Weight | | |
| Total Dimension | 60X44X24cm | 60X44X24cm |
| Total Weight | 12 kg | 12 kg |
| | | |
| Warrant | | |
| 12 month | 12 month | 12 month |

Welcome to customize your balloon & brand

Tichuan International Co.,Ltd

Website: <https://www.ti-chuan.com>

Email: contact@ti-chuan.com.cn

Mobile:0086 18626302806

Address: No.29-2 Luou Road,Hudai Industry Park,
Binhu District,Wuxi city 214126

Online:

Skype: forestchina1983

QQ: 718782827

Wechat | Whatsapp: 0086 18626302806

Technical Support:

support@ti-chuan.com

